

HYPERline Series

Wall Mounting 19" Cabinets



Compliance:

- EN 12150-1 Compliant Tempered, anti-static, secure, grinded edges Glass front door- t:4,0mm
- DIN 1743, DIN 53571, RoHS Compliant barrel quarter turn lock
- EN 60297 Mechanical structures for electrical and electronic equipment. Dimensions of mechanical structures of the 482,6 mm (19 in) series
- EN 60917 Modular order for the development of mechanical structures for electronic equipment practices. Generic standard
- EN 61587-1 Mechanical structures for electronic equipment Tests for IEC 60917 and IEC 60297 series - Part 1: Environmental requirements, test set-up and safety aspects for cabinets, racks, subracks and chassis under indoor conditions
- Climatic and Environment: EN 61587-1/4.2, IEC60068-2-1, IEC60068-2-2, IEC60068-2-30,
- Static Mechanical Load Lifting: EN 61587-1/5.2.1
- Static Mechanical Load Stiffness: EN 61587-1/5.2.2
- Dynamic Mechanical Load Vibration and Shock, Impact: EN61587-1/5.3.1,EN61587-1/5.3.3,IEC60068-2-6, IEC60068-2-27,
- Earth Bond: EN61587-1/6.2
- Flammability: EN 61587-1/6.3
- Degrees Of Protection Provided By Enclosures (Ip Code): IP20, EN61587-1/6.4
- EN 13501-1+ A1- Epoxy Powder coated compliant to Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests
- Epoxy Powder coating tested as per EN ISO 9227 Corrosion tests in artificial atmospheres - Salt spray tests, EN ISO 2409 Paints and varnishes - Cross-cut test, EN ISO 2178 Non-magnetic coatings on magnetic substrates Measurement of coating thickness - Magnetic method
- RoHS Compliacy according to 2011/65/EU
- CE Compliant to EN 60950-1
- Sheet Steel Compliant to EN 10130 Cold Rolled Sheet Steel with DC-01 6112 or 7122 grade
- Fixing elements are compliant to Connection elements (bolt, nuts, shim, etc.) "DIN 7985, DIN 965, DIN 7981, DIN 934, DIN 985, DIN 933-coated according to EN ISO 2081 Metallic and other inorganic coatings - Electroplated coatings of zinc with supplementary treatments on iron or steel

• Production Standards


ISO 9001- Quality Management System ISO 14001- Environmental Management System















Bottom view










Front view


Side view


Rear view



Part Definition	Material Quality	Material Thickness (mm)	Shipment Configuration
Main body (Structure)	DIN EN 10130-DC-01-6112 CRS	0,8 mm	1
Front Door	EN 12150-1 Tempered Secure Glass	4 mm	1
19" Equipment Mounting Rails	DIN EN 10130-DC-01-6112 CRS	1,5 mm	2
Rear Panel	DIN EN 10130-DC-01-6112 CRS	1,2 mm	1
Side Panels	DIN EN 10130-DC-01-6112 CRS	0,8 mm	2
Side Frame Module	DIN EN 10130-DC-01-6112 CRS	0,8 mm	2








Max / min equipment mounting distance (450)

Max / min equipment mounting distance (600)



Dimensions in width and height

HYPERline Series - Wa	ıll Mounting 19" Cabinets W600mm x D450	mm				
Product Number	Description	U Height	Ah Wall Assembly Height mm	h Inner Height mm	H Outer Height mm	Depth mm
LN-HL-04U6045-CC-A/F	04U 19" W600xD450mm Wall Mounting Cabinet	04U	135	235	239	450
LN-HL-07U6045-CC-A/F	07U 19" W600xD450mm Wall Mounting Cabinet	07U	268	368	372	450
LN-HL-09U6045-CC-A/F	09U 19" W600xD450mm Wall Mounting Cabinet	09U	357	457	461	450
LN-HL-12U6045-CC-A/F	12U 19" W600xD450mm Wall Mounting Cabinet	12U	490	590	594	450
LN-HL-15U6045-CC-A/F	C-A/F 15U 19" W600xD450mm Wall Mounting Cabinet		624	724	728	450
LN-HL-18U6045-CC-A/F 18U 19" W600xD450mm Wall Mounting Cabinet			757	857	861	450
HYPERline Series - Wall Mounting 19" Cabinets W600mm x D600mm						
Product Number	Description	U Height	Ah Wall Assembly Height mm	h Inner Height mm	H Outer Height mm	Depth mm
LN-HL-04U6060-CC-A/F	04U 19" W600xD600mm Wall Mounting Cabinet	04U	135	235	239	600
LN-HL-07U6060-CC-A/F	07U 19" W600xD600mm Wall Mounting Cabinet	07U	268	368	372	600
LN-HL-09U6060-CC-A/F	09U 19" W600xD600mm Wall Mounting Cabinet	09U	357	457	461	600
LN-HL-12U6060-CC-A/F	_N-HL-12U6060-CC-A/F 12U 19" W600xD600mm Wall Mounting Cabinet		490	590	594	600
LN-HL-15U6060-CC-A/F 15U 19" W600xD600mm Wall Mounting Cabinet		15U	624	724	728	600
LN-HL-18U6060-CC-A/F	18U 19" W600xD600mm Wall Mounting Cabinet	18U	757	857	861	600




Other Features and Details:

Side panels in shipping configuration being delivered with 2 pcs side panel closure lock hole- which allows by finger to lift off the side panels. Incase required more Security in side panels extra set of barrel side panel quarter turn lock can be ordered.

2 Options for side panel closure lock hole


- 1) Default (Shipping configuration) plastic lock hole closure
- 2) Lock for side panel (O-type)



Plastic lock hole closure.

It does not lock the side closure. It allows you to open the side closure by simply pulling it up with your finger.

It does lock the side panel closure.



Other Features and Details:

Lock on front door has a plastic handle housing the Lande Logo.

Other Features and Details:

Front glass door opens at 115 degree angle.








Other Features and Details:

Side panels holds the side frame with its hooks to incase security. The side panels can be equipped with barrel quarter turn lock with





Other Features and Details:

Flat pack helps saving logistics and warehousing costs.







Other Features and Details:

Lock on front door has a plastic handle housing the Lande Logo.





Other Features and Details: Rubber glass door stoppers.



HYPERline Series - Wall Mounting 19" Cabinets Accessories

Fan Modules for wall Mounting, Ready pre-installed, plug-in and run style, with on/off switches or with analog thermostat and plugs. Each Fan has an air flow capacity of 2,3-3 cbm/min. Fan Technical data: 18/17 W, 220/240 VAC, 50/60 Hz, 013/0,11 A,2300/3000 rpm 42 dB noise level, Fan life: 50.000 hours







FAN MODULE ON/OFF SWITCHED BALL BEARING LONG LIFE FAN-50.000 hours- HIGHEND DESIGN -CONCEPT-AND TECHNICAL CHARACTERISTICS

Part Nr	Series	Product Description
LN-FAN-ONF-1FWM-CC	ACCESSORY	1 Fan Module on/off switched Wall Mounting Type
LN-FAN-ONF-2FWM-CC	ACCESSORY	2 Fan Module on/off switched Wall Mounting Type

^{***} Add UK notation at the end of Part Number- example LN-FAN-ONF-1FWM-BL-UK for UK BS1363 Plug **** CC= Color codification- Replace CC with BL for Black RAL 9005 Color- and Replace CC with LC for Light Grey RAL 7035 Color

FAN MODULE THERMOSTAT SWITCHED BALL BEARING LONG LIFE FAN-50.000 hours- HIGHEND DESIGN -CONCEPT-AND TECHNICAL CHARACTERISTICS

Part Nr	Series	Product Description	
LN-FAN-THM-1FWM-CC	ACCESSORY	1 Fan Module thermostat switched Wall Mounting Type	
LN-FAN-THM-2FWM-CC	ACCESSORY	2 Fan Module thermostat switched Wall Mounting Type	

^{***} Add UK notation at the end of Part Number- example LN-FAN-THM-1FWM-BL-UK for UK BS1363 Plus **** CC= Color codification- Replace CC with BL for Black RAL 9005 Color- and Replace CC with LC for Light Grey RAL 7035 Color

FAN MODULE ON/OFF SWITCHED BALL BEARING LONG LIFE FAN-50.000 hours ECONOMIC

Part Nr	Series	Product Description
LN-FAN-BB-1FPR-CC	ACCESSORY	1 way Fan Module On/off Switched RAL 9005 Black
LN-FAN-BB-2FPR-CC	ACCESSORY	2 way Fan Module On/off Switched RAL 9005 Black


^{**} Add UK notation at the end of Part Number- example LN-FAN-BB-1FPR-BL-UK for UK BS1363 Plug *** CC= Color codification- Replace CC with BL for Black RAL 9005 Color- and Replace CC with LC for Light Grey RAL 7035 Color

FAN MODULE THERMOSTAT CONTROLLED BALL BEARING

LONG LIFE PAN-30,000 Hours ECONOMIC			
Part Nr Series		Product Description	
LN-FAN-BB-1FPT-CC	ACCESSORY	1 way Fan Module Thermostat Controlled RAL 9005 Black	
LN-FAN-BB-2FPT-CC	ACCESSORY	2 way Fan Module Thermostat Controlled RAL 9005 Black	

^{***} Add UK notation at the end of Part Number- example LN-FAN-BB-1FPT-BL-UK for UK BS1363 Plug **** CC= Color codification- Replace CC with BL for Black RAL 9005 Color- and Replace CC with LC for Light Grey RAL 7035 Color





ECONOMIC EXTENDABLE FAN MODULES- NO ANY METAL HOUSING BALL BEARING LONG LIFE FAN-50.000 hours ECONOMIC+

Part Nr	Series	Product Description
LN-FAN-HL-1FBB-M	ACCESSORY	Single Fan- with Grill- 1,8meter Power Cable DIN49441 Schuko Plug and Extention Terminal Male- Ball Bearing Long life Fan
LN-FAN-HL-1FBB-E	ACCESSORY	Single Fan- with Grill- Extention Terminal Female Ball Bearing Long life Fan

LN-FAN-HL-1FBB-E is Just a fan for making cabinet equipped with 2 fans- used with main product LN-FAN-HL-1FBB-M and add the extention fan

SIDE PANEL BARREL LOCK SET

Part Nr	Series	Product Description
LN-LOCK-KIT-HPL	ACCESSORY	1 set 2 pcs Side Panel Barrel Lock Set

^{**} Side panels are equipped with plastic lock hole closure- which allows your finger to lift of side panels. Incase more security is required a set of LN-LOCK-KIT-HPL to be ordered per cabinet.

FOUIPMENT MOUNTING RAILS for HYPERline WALL CABINETS

EQ		OUNTING RAILS IN ITTERMIC WALL CADINETS
Part Nr	Series	Product Description
LN-PRF-CMD-04UEU-ZN	ACCESSORY	4U 19" Equipment Mounting Rails 1set:2pcs (left/right) HYPERline Wall Mounting Type
LN-PRF-CMD-07UEU-ZN	ACCESSORY	7U 19" Equipment Mounting Rails 1set:2pcs (left/right) HYPERline Wall Mounting Type
LN-PRF-CMD-09UEU-ZN	ACCESSORY	9U 19" Equipment Mounting Rails 1set:2pcs (left/right) HYPERline Wall Mounting Type
LN-PRF-CMD-12UEU-ZN	ACCESSORY	12U 19" Equipment Mounting Rails 1set:2pcs (left/right) HYPERline Wall Mounting Type
LN-PRF-CMD-15UEU-ZN	ACCESSORY	15U 19" Equipment Mounting Rails 1set:2pcs (left/right) HYPERline Wall Mounting Type
LN-PRF-CMD-18UEU-ZN	ACCESSORY	18U 19" Equipment Mounting Rails 1set:2pcs (left/right) HYPERline Wall Mounting Type

^{**} All HYPERline Wall Mounting Cabinets supplied with 2 pcs 19" Equipment mounting Rails in Front, for additional set of 19" rails, please order as accessory from above list.





^{***} Add UK notation at the end of Part Number- example L.N-FAN-HL-1FBB-M-UK for UK BS1363 Plug